

# MATERIAL SAFETY DATA SHEET

LANIER  
2300 PARKLAKE DRIVE, NE  
ATLANTA, GA 30345-2979  
EMERGENCY TELEPHONE:  
(404) 621-1395 (8am-6pm)  
(800) 333-2679 (6pm-8am)

SUPERSEDES: 78696922133

ISSUED: AUGUST 1986  
DOCUMENT NO: FX-004  
DUNS NO: 150634004

DPI I.D. NUMBER: U78803592472

**1. PRODUCT IDENTIFICATION**

CHEMICAL FAMILY: Isoparaffinic Hydrocarbons	TRADE NAME: Type 446 Toner Premix
--	--------------------------------------

DEPARTMENT OF TRANSPORTATION PROPER SHIPPING NAME:  
N/A

DEPARTMENT OF TRANSPORTATION HAZARD CLASS:  
N/A

2. INGREDIENTS	PERCENT	CAS NO.	EXPOSURE LIMITS	SOURCE*
Isoparaffinic Hydrocarbons	99.0	64742-48-9	300 ppm	E
Carbon Black	<1.0	1333-86-4	3.5 MG/M <sup>3</sup>	E

\* SOURCE OF EXPOSURE LIMIT DATA:  
 A. ACGTH THRESHOLD LIMIT VALUES      B. FEDERAL OSHA PERMISSIBLE EXPOSURE LIMIT  
 C. LANIER GUIDELINES                      D. MANUFACTURER RECOMMENDED GUIDELINES  
 E. NONE ESTABLISHED                      N/A = NOT APPLICABLE                      N/D = NOT DETERMINED

**3. PHYSICAL DATA**

BOILING POINT: 157 - 176°C      °F	SOLUBILITY IN H <sub>2</sub> O: Nil
VAPOR PRESSURE: < 10 AT 25°C      °F	SPECIFIC GRAVITY (H <sub>2</sub> O=1): 0.76 - 0.8
VAPOR DENSITY: 5.0 (AIR = 1)	pH: N/A
EVAPORATION RATE: 0.45 (ETHER = 1)	VISCOSITY: N/D
% VOLATILE: N/A	

APPEARANCE AND ODOR: Black liquid. Mild hydrocarbon odor.

**4. FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT (TEST METHOD): 104°F (Tag closed cup)	FLAMMABILITY LIMITS: LEL = 0.7%      UEL = 7.0%
--	--

EXTINGUISHING MEDIA:  
Dry chemical, foam, carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES:  
Normal procedures for combustible liquids

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not mix or store with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

**5. REACTIVITY DATA**

STABILITY:    STABLE <input checked="" type="checkbox"/> UNSTABLE <input type="checkbox"/>	HAZARDOUS POLYMERIZATION:    MAY OCCUR <input type="checkbox"/> MAY NOT OCCUR <input checked="" type="checkbox"/>
--	---

INCOMPATIBILITY - MATERIALS TO AVOID:  
Strong oxidizers

CONDITIONS TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCTS:  
Fumes, smoke, carbon dioxide, aldehydes and other decomposition (in case of incomplete combustion).

# MATERIAL SAFETY DATA SHEET

TRADE NAME: Type 446 Toner Premix		DATE: August 1986
6. ENVIRONMENTAL INFORMATION		
SPILL RESPONSE: (OBSERVE ALL PRECAUTIONS IN SECTION 7): Remove ignition sources. Remove free liquids, add absorbent. Ventilate confined spaces. Do not breathe vapor.		
RECOMMENDED DISPOSAL: Assure conformity with applicable governmental regulations.		
ENVIRONMENTAL DATA: N/D		
7. PRECAUTIONARY INFORMATION		
Keep away from strong oxidants. Do not store near heat or flame. Use in ventilated area. Close containers when no in use.		
8. HEALTH HAZARD DATA	9. SUGGESTED FIRST AID	
EYE CONTACT:	Flush with water for 15 minutes or until irritation subsides. If persists, call a physician.	
SKIN CONTACT:	Wash skin with soap and water. Remove contaminated clothing.	
INHALATION:	If overcome, remove from exposure. Call a physician.	
IF SWALLOWED:	DO NOT INDUCE vomiting, call a physician.	

THE INFORMATION ON THIS DATA SHEET REPRESENTS OUR CURRENT DATA AND BEST OPINION AS TO THE PROPER USE IN HANDLING OF THIS PRODUCT UNDER NORMAL CONDITIONS. USING THE PRODUCT WHICH IS NOT IN CONFORMANCE WITH THIS DATA SHEET OR WHICH INVOLVES USING THE PRODUCT IN COMBINATION WITH ANY OTHER PRODUCT OR ANY PROCESS IS THE RESPONSIBILITY OF THE USER.