

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29CFR 1910.1200. Standard must be
consulted for specific requirements.

FDNo.39-SILICON
U.S. Department of Labor
Occupational Safety and Health
Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Silicone Oil Kit - PENGUIN OILER
4407673280 78-8037-1756-6

Section I

Manufacturer's Name Toshiba Corporation Yanagicho Works	Emergency Telephone Number
Address (Number, City, State, and ZIP Code) 70, Yanagi-cho, Saiwai-ku, Kawasaki-shi, 210 Japan	Telephone Number for Information 044-548-5600
	Date Prepared January 7, 1994
	Signature of Preparer (Optional) Toshimichi Ishizawa

Section II - Ingredients / Identity Information

Components (Specific Chemical Identity; Common Name(s))	CAS No.	OSHA PEL	ACGIH TLV	%
Polyalkyl (C ₁₋₂₀) siloxane	63148-62-9	n.a.	n.a.	99
Ferric compound	19583-54-1	n.a.	n.a.	1 or less

Section - III - Physical/Chemical Characteristics

Boiling Point	N.A.	Specific Gravity(H ₂ O=1)	0.97
Vapor pressure (mmHg.)	Neg.	Melting Point	N.A.
Vapor Density (AIR=1)	N.A.	Evaporation Rate (Butyl Acetate=1)	Neg.
Solubility in Water	Not soluble		
Appearance and Odor	Colorless, transparent and oderless fluid.		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	200 degree C Min. (Open cut)	Flammable Limits	LEL	UEL
		Not measured	n.a.	n.a.
Extinguishing Media	Foam, dry chemical or carbon dioxide			
Special Fire Fighting Procedures	Not required			
Unusual Fire and Fighting Procedures	None			

(Reproduce locally)

