

# LANIER IM C2000 IM C2500

Copier  Printer  Facsimile  Scanner



## 11" x 17" Multifunction Color

Take advantage of technology that scales and flexes as your business needs do. Be more productive and efficient with the LANIER IM C2000/C2500 range of 11" x 17" color devices.

### It's time to:

- Print speeds of 20 - 25 ppm.
- Easy-to-use 10.1" Smart Operation Panel with intuitive menu.
- Mobile connectivity options — including NFC, AirPrint® or Mopria.
- Increased uptime and performance — with Intelligent Support.

Access a range of productivity features and upgrades — such as scanning directly to your email or dedicated folders on your network and ensure you have the latest security enhancements and mobile device connectivity options. Our Intelligent Devices are designed to do more as and when your business needs to do more, using technology that's scalable, secure, sustainable and simple.

### Get more from your Intelligent Devices:

- Tailor settings to individual users — for quick access to apps used most often.
- Work more efficiently — with expanded paper tray capacity.
- Automatic firmware upgrades — providing maximum security.

LANIER Intelligent Devices remain current and relevant no matter what your workplace requires. This way, you have ready and easy access to new functionality, when needed. Environmentally-friendly low TEC (Typical Electricity Consumption) values deliver reduced energy consumption and cut running costs, while Intelligent Support features such as Predictive Maintenance mean that device performance is monitored and any fixes resolved swiftly — minimizing the impact on your workplace.

### All Intelligent Devices provide:

- Quick access to Web Help Tools via Intelligent Support.
- A consistent user interface and experience across your Lanier fleet.
- Easy integration with third party solutions.
- Regular functionality upgrade releases to do more, smarter and faster.

Ready to take a swipe at a faster way to work? Our range of Intelligent Devices come fitted with a 10.1" Smart Operation Panel designed to enhance your productivity, mobility and environmental commitment. Experience a user interface that offers fast and simple navigation with the ability to customize the layout to best suit your needs — even by adding your own company branding. Access device features, move between jobs and tasks quickly and conveniently enable teams to work smarter.



# LANIER IM C2000/IM C2500

## MAIN SPECIFICATIONS

	IM C2000	IM C2500
<b>GENERAL</b>		
Warm-up time		21 seconds
First output speed: B/W		5.1 seconds
First output speed: full color		7.4 seconds
Continuous output speed	20 ppm	25 ppm
Memory: standard		2 GB
Memory: maximum		4 GB
HDD: standard		320 GB
HDD: maximum		320 GB
ARDF capacity		100 sheets
Weight	200.6 lbs / 91 kg	200.6 lbs / 91 kg
Dimensions: W x D x H		587 x 685 x 913 mm, 23.1" x 27.0" x 35.9"
Power source		120V - 127V 60Hz
<b>COPIER (STANDARD)</b>		
Multiple copying	Up to 999 copies	
Resolution	600 dpi	
Zoom	From 25% to 400% in 1% steps	
<b>PRINTER (STANDARD)</b>		
CPU	Intel Apollo Lake 1.3GHz	
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)	
Printer language: option	Genuine Adobe® PostScript® 3™, PDF Direct from Adobe®	
Print resolution	Up to 1,200 x 1,200 dpi	
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B	
Network interface: option	Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)	
Mobile printing capability	Apple AirPrint®, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector	
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012R2, Windows® Server 2016	
Mac OS environments	Macintosh OS X v10.11 or later	
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX	
SAP® environments	SAP® R/3®, S/4®	
Other supported environments	IBM iSeries AS/400 using OS/400 Host Print Transform	
<b>SCANNER (STANDARD)</b>		
Scanning speed	80 ipm (simplex)	
Resolution: maximum	Up to 1,200 dpi	
Compression method	TIFF (MH, MR, MMR, JBIG2), Grayscale	
File formats	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encryption PDF, OCR* Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encryption PDF, OCR* * Requires optional OCR Unit Type M13	
Scan modes	E-mail, Folder, USB, SD Card	
<b>FACSIMILE (OPTIONAL)</b>		
Circuit	PSTN, PBX	
Transmission speed	2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission)	
Modem speed: maximum	33.6 Kbps	
Resolution: standard	8 x 3.85 line/mm, 200 x 100 dpi	
Resolution: option	16 x 15.4 line/mm, 400 x 400 dpi	
Compression method	MH, MR, MMR, JBIG	
Scanning speed	68 spm	
Memory: standard	4 MB (320 pages)	
Memory: maximum	60 MB (4,800 pages)	
<b>PAPER HANDLING</b>		
Recommended paper size	Tray 1: 8-1/2" x 11" (A4) Tray 2: 5-1/2" x 8" - 12" x 18" (SRA3, A3 - A6, B4 - B6), Envelopes Bypass tray: Up to 12" x 18", Envelopes, Custom Sizes [Width: 3.5" - 12.6" (90 - 320 mm), Length: 5.8" - 49.6" (148 - 1260 mm)]	
Paper input: standard	1,200 sheets	
Paper input: maximum	2,300 sheets	
Paper output: standard	500 sheets 8.5" x 11" (A4) or smaller; 250 sheets (B4) or larger	
Paper output: maximum	1,625 sheets	
Paper weight	Trays: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m²) Bypass: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²) Duplex: 14 - 45 lb. Bond/142 lb. Index (52 - 169 g/m²)	
Paper types	Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP, Gloss	

# LANIER IM C2000/IM C2500

## MAIN SPECIFICATIONS

	IM C2000	IM C2500
<b>ECOLOGY</b>		
Power consumption: maximum	Less than 1,584 W	
Power consumption operation: B/W	422.5 W	454.7 W
Power consumption operation: full color	462.3 W	498.5 W
Power consumption: ready	45.2 W	
Power consumption: sleep	0.54 W	
TEC <sup>1</sup>	0.24 kWh	0.29 kWh
ENERGY STAR®	Certified	
EPEAT®	Gold Rated*	
	* EPEAT Gold rating is applicable only in the USA.	

### OUTPUT TRAYS AND FINISHER OPTIONS

1 x 550-sheet Paper Tray (PB3270)	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m <sup>2</sup> )
2 x 550-sheet Paper Tray (PB3300)	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m <sup>2</sup> )
1,000-sheet Booklet Finisher (SR3270)	Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Booklet Tray: 8.5" x 11" to 12" x 18" (A4 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ); Stack capacity: 1,000 sheets; Staple capacity: 50 sheets; Staple paper size: Normal Staple: 8.5" x 11" to 12x18" (A4 - A3); Saddle Stitch: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 staples, Booklet
250-sheet Internal Finisher (SR3300)	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ), Stack capacity: 250 sheets, Staple capacity: 5 sheets, Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3), Staple paper weight: 17 - 21 lb. Bond (64 - 80 g/m <sup>2</sup> ), Staple positions: Top
500-sheet Internal Finisher (SR3250)	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ); Stack capacity: 500 sheets; Staple capacity: 50 sheets; Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 staples
Internal Shift Tray (SH3080)	Tray capacity: 250 sheets with 80g/m <sup>2</sup> paper (A4, LT or smaller), 125 sheets with 80g/m <sup>2</sup> paper (B4, LG or larger), Paper size: 12.60" x 23.62" or smaller, Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> )
One-bin Tray (BN3130)	Tray capacity: 125 sheets, Paper size: 5.5" x 8.5" to 12" x 18" (A5 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> )

### OTHER OPTIONS

Fax Option Type M37, G3 Interface Unit Type M37, Memory Unit Type M37 4GB, Cabinet Type F, Caster Table Type M3, VM CARD Type M37, Punch units (PU3070, PU3080), PostScript3 Unit Type M37, IEEE 802.11a/g/n Interface Unit Type M19, Device Server Option Type M37, File Format Converter Type M19, OCR Unit Type M13, Imageable Area Extension Unit Type M19, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built-in Unit Type M37, ESP XG-PCS-15D, External USB Keyboard (No Bracket), FAX Memory Unit Type M19 64MB, Bridge Unit BU 3090, Banner Paper Guide Tray Type M19

### CONSUMABLES

Toner: black	16,500 prints
Toner: cyan/magenta/yellow	10,500 prints
Consumable yield measuring method based on A4, 5% coverage	

<sup>1</sup> TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Lanier parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard  
Exton, PA 19341



1-855-5-LANIER



www.lanier.com

**LANIER**

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-855-5-LANIER  
©2019 Ricoh USA, Inc. All rights reserved. Lanier™ and the Lanier logo are trademarks of Ricoh USA, Inc. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company Ltd. All other trademarks are the property of their respective owners. Lanier products and services are offered by Ricoh USA, Inc. and its affiliates. The content of this document, and the appearance, features and specifications of Lanier products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Lanier products and services are as set forth in the express warranty statements accompanying them.

L4025-2